

# COUNTRY SDN





COUNTRY SDN 65230



COUNTRY SDN 65231



COUNTRY SDN 65240



COUNTRY SDN 65241



COUNTRY SDN 65242



COUNTRY SDN 65244



COUNTRY SDN 65250



COUNTRY SDN 65251



COUNTRY SDN 65255

## Technical details carpet tiles

Manufacturing type	<b>tufted 1/10"</b>		
Construction			<b>loop pile</b>
Pile composition			<b>100% PA 6</b>
Dye method			<b>solution dyed</b>
Primary backing			<b>polyester fleece</b>
Secondary backing			<b>GREENBASE modified bitumen</b>
Pile weight	ISO 2424	g/m <sup>2</sup>	<b>550</b> (+/-)
Total weight	ISO 8543	g/m <sup>2</sup>	<b>4.100</b> (+/-)
Pile height	ISO 1766	mm	<b>1,0</b> (+/-)
Total height	ISO 1765	mm	<b>5,5</b> (+/-)
Tuft density	ISO 1763	/m <sup>2</sup>	<b>164.000</b> (+/-)
Size		cm	<b>50 x 50</b>
Packing			<b>20 per box 5 m<sup>2</sup></b>
Classification	EN 1307		<b>33 heavy commercial</b>
Comfort rating	EN 1307		<b>LC 1</b>
Castor chair	EN 985		<b>A (intensive)</b>
Dimensional stability	EN 986		<b>≤ 0,2%</b>
Fire resistance	EN 13501-1		<b>Bfl-S1</b> loose laid
Permanent antistatic	ISO 6356	kV	<b>≤ 2,0</b>
Transversal resistance	ISO 10965	Ω	
Thermal resistance	ISO 8302	m <sup>2</sup> /K/W	
Sound absorption	ISO 354	α <sub>w</sub>	
Impact sound reduction	ISO 10140	ΔL <sub>w</sub>	
	ISO 10140	ΔL	(1000 Hz)
Light fastness	ISO 105 B02		<b>8</b>
Rubbing fastness	ISO 105 X12		<b>4-5</b> wet/dry
Water fastness	ISO 105 E01		<b>5</b> colour/staining

